

# RADIOGRAPHIC GENERATOR

 Produced and designed in Italy by Foschi

**NEW!**


 **ARIA**<sup>®</sup> 450 *digital*



Collimator LED light that can be activated remotely or by pedal




4-way Floating table



Cesium Flat Panel detector with 43x43 cm of sensitive area  
**THALES**

Mechanical anti-trip brake



20002176

ARIA 450 digital + kit pc

22002176

ARIA 450 digital + kit workstation

The **ARIA450 Digital** generator is the first radiological with a fully integrated flat panel created for the Veterinary medicine market.

With **17"x17"** inches sensitive area the **THALES Flat Panel** detector connected to the generator allows you to perform complex studies in an automated way, reducing the learning curve and maximizing image quality from the first use.

The **ARIA software** acts as a single console for managing the entire device, allowing dose selection and image acquisition in just 5 seconds.

The graphical user interface has been revisited and is even more intuitive and simple. You can choose between over 1,000 presets for 11 different species: by choosing the anatomical width or the size of the breed, **ARIA** will load the ideal exposure for the highest image quality with the lowest dose.

Thanks to **Foschi and Thales**, high technologies the system has the possibility to receive **remote assistance**. Using remote assistance software is the fastest and most efficient means of resolving technical problems.

With the new **ARIA 450 Digital**, the **ARIA** family is even **smarter!**

## CARATTERISTICHE

 *Prodotto in Europa*

	<b>ARIA 4343 THALES</b>
Detection Area	17x17 inch
Scintillator	CsI
Connection	Ethernet 1000Base-T
Dimensions (W x L x D)	500 x 488.5 x 15.0 mm
Pixel	2880x2880
Pixel Pitch	148 µm
AD conversion	16 bit
Dqe @ 0 Lp/Mm_2 µgy	> 70%
Acquisition time	5 sec

- + **AUTOMATED DOSE**
- + **EFFECTIVE ON ALL PATIENTS**
- + **17''x 17'' THALES FLAT PANEL DETECTOR TOTALLY INTEGRATED**
- + **TOTALLY MANAGING BY ARIA SOFTWARE**
- + **REMOTE ASSISTANCE**

## CARATTERISTICHE

 *Prodotto in Italia da Foschi*

	<b>ARIA 450 digital</b>
Max current	450 mA
Max Voltage	125 kV
Max Power	32 kW
Working Frequency	100 kHz
kV Rang	From 40 to 125
mAs Range	From 0.5 to 150
Focal Spot	0.6 and 1.3 mm
Remote Assistance	Active
Collimator	Cold light LED

